



## CE-DVR1-2GB

Single Channel Mini DVR with Built-In Camera

- Portable Compact Size
- Built-in 480 TVL Resolution C-MOS Camera
- Continuous and Motion Detection Recording
- Built-in 2GB Flash Memory
- User Friendly
- Bracket, Video Cable, and Power Supply Included
- DC12V or 4 x AA Batteries (4 hours 45 mins. Average battery life)

## **Storage Capacity**

| <b>Quality Level</b> | 640 x 480 at 12 FPS | 320 x 240 at 30 FPS |
|----------------------|---------------------|---------------------|
| High                 | 7.9 hrs.            | 13.9 hrs.           |
| Medium               | 15.2 hrs.           | 17.1 hrs.           |
| Low                  | 25.3 hrs.           | 34.8 hrs.           |

<sup>(</sup>Approximate Recording Times: Motion Recording will greatly affect time based on the amount of motion activity.)

## **Specifications**

| Specifications            |   |  |
|---------------------------|---|--|
| Camera                    | CE-DVR1-2GB   |  |
| Image Sensor              | 1/4" Color C-MOS  |  |
| Resolution                | 480 TV Lines  |  |
| Video Format              | NTSC / PAL  |  |
| S/N Ratio                 | 46dB  |  |
| <b>Electronic Shutter</b> | 1/60 ~ 1/15,000 sec.  |  |
| Lens                      | 3.8mm / F2.0  |  |
| White Balance Control     | Auto  |  |
| Gain Control              | Auto  |  |
| DVR                       |   |  |
| Video Compression         | MPEG4   |  |
| Recording Resolution      | VGA (640 x 480) at 12 FPS /<br>QVGA (320 x 240) at 30 FPS     |  |
| Recording Quality         | High / Medium / Low   |  |
| Recording Mode            | Continuous / Motion Detection                                 |  |
| Storage Capacity          | Built-In Flash Memory (2GB)                                   |  |
| Memory Full               | Selectable Function: Full Stop / Overwrite                    |  |
| Playback Mode             | Forward / Rewind: 1x / 4x / 8x / 16x / 32x,<br>Pause and Stop |  |
| Search Method             | Date and Time   |  |
| <b>Motion Detection</b>   | Full Screen / Adjustable Detect Sensitivity<br>Rate 1 ~ 99    |  |
| On Screen Display         | Mode / Date / Time / Status / Set-up Menu                     |  |
| Video Output              | 1.0 Vp-p, 75Ω   |  |
| Power Consumption         | 2.0 Watts Max.  |  |
| Power Requirement         | DC12V or 4 x AA Batteries                                     |  |
| Dimensions                | 3.93"(H) x 2.76"(W) x 1.41"(D)                                |  |
|                           |   |  |

Information in this document is subject to change

## **Recommended Power Supply**

All Clinton Electronics DC12V or 4x AA Batteries (Power Supply Included)