



CO1224A Carbon Monoxide Alarm

System Sensor's CO1224A provides early warning when its electrochemical sensing technology accurately measures carbon monoxide levels in the air.



Carbon monoxide is an odorless, colorless, tasteless and highly toxic gas that is produced when fuels, such as wood, gasoline, charcoal and oil, are burned with insufficient air. The majority of residential and commercial fatalities caused from these fuels come from heating systems, power tools and charcoal grills.

If carbon monoxide is detected, the CO1224A will alert residents by sounding and flashing a temp-4 signal alarm. Additional protection is provided with built-in alarm and trouble contacts which can be used for monitoring. This can provide protection regardless of whether residents are away from home, sleeping or already suffering from the effects of CO. The alarm contact has a 10 second delay so the unit can be tested with the test pushbutton without activating the alarm contact.

The CO1224A trouble relay can send a sensor failure or end-of-life signal to the control panel and the central station. SEMS-type terminal Philips-head screws provide a quicker and more positive wiring connection and code required wiring supervision. Also, the CO1224A offers a low current draw, allowing more detectors to be connected to the panel without having to purchase a more expensive panel or an extra power supply.

Because the CO1224A is a 12/24 VDC detector, it will operate on most industry security or fire alarm control panels.

Features

- Full compliance with CSA 6.19-01
- Alarm/Trouble contacts
- Wiring supervision with SEMS terminals
- A six-year end-of-life indication
- 12/24 VDC
- A current draw of 20mA in standby and 40mA in alarm
- Versatile mounting for wall and ceiling
- Electrochemical sensing technology

Agency Listings



6.19-01

Specifications

Architectural/Engineering Specifications

Carbon monoxide alarm shall be a System Sensor model number CO1224A, listed to ULC in compliance with CSA 6.19-01. The detector shall be equipped with an alarm/trouble sounder, alarm/trouble relay, and test/silence pushbutton. The alarm relay shall have a 10 second delay. The detector's base shall be able to mount to a single-gang electrical box or direct (surface) mount to the wall or ceiling. Wiring connections shall be made by means of SEMS screws. The detector shall provide LED indicators, which blink to indicate normal standby, alarm, or trouble/end-of-life conditions. When the sensor supervision is in a trouble condition, the detector shall sound an audible trouble signal and activate the trouble relay. When the detector gives a trouble or end-of-life signal, the detector shall be replaced.

Electrical Specifications

Operating Voltage	12/24 VDC
Audible Signal	85 dB in alarm MIN.
Standby Current	20 mA
Alarm Current	40 mA (75 mA test)
Alarm Contact Ratings	0.5 A @ 30 VDC
Trouble Contact Ratings	0.5 A @ 30 VDC

Physical Specifications

Size	Length: 5.1", Width: 3.3", Height: 1.3"
Approximate Weight	7 oz
Operating Temperature Range	0° – 40° C (32° – 104° F)
Operating Humidity Range	22 – 90% RH
Input Terminals	14 – 22 AWG
Mounting	Single-gang back box; surface mount to wall or ceiling

Operation Modes

Operation Mode	Green LED	Red LED	Sounder
Normal (standby)	Blink 1 per minute	—	—
Alarm	—	Blink in temp 4 pattern	Sound in temp 4 pattern
Trouble	—	Blink once per minute	Sound once per minute

Hush Feature: Pushing the Test/Hush button will silence the sounder for 5 minutes.

Trouble Feature: When the detector is in a trouble condition, it will sound a trouble signal and activate the trouble relay.

End-of-life Timer: After the sensor inside the detector has reached the end of its useful life, a trouble signal will sound and the trouble contact will activate. This will indicate that it is time to replace the detector. An electrochemical carbon monoxide detector lifespan is approximately six years, and the detector must be replaced by the date marked on the inside of the product.

Ordering Information

Part No.	Description
CO1224A	12/24 volt, 4-wire carbon monoxide alarm



6-6581 Kitimat Road • Mississauga ON, L5N 3T5
Phone: 800-SENSOR2 • www.systemsensor.ca

©2007 System Sensor.
Product specifications subject to change without notice. Visit systemsensor.com for current product information, including the latest version of this data sheet.
A05-0402-002 • 3/07 • #1772